

HERMACOLOR GREEN GR6016

Product Description

HERMACOLOR GREEN GR6016 is composed of thermoplastic microcapsules blended with a carrier. The thermo chromic pigment is compatible with PE, HDPE, PP, PS, SAN, TPU; TPE. It is incompatible with PET and PC. This product has been designed to be suitable for Blown- and cast film, injection molding, blow molding and sheet.

Specifications

Properties	Method	Typical values
Carrier Resin	Hermess compounds laboratory	PE
Dispersion	Hermess compounds laboratory	Excellent

Recommendations of use

Addition levels of **HERMACOLOR GREEN GR6016** depend on various factors such as thickness of the article, expected service life, presence of fillers and other additives and commonly range from **0.5-8%**.

Contact us for your specific recommendation needs

Packaging

HERMACOLOR GREEN GR6016 is supplied in plastic bags on 1000kg or 1375kg wooden pallets.

Storage Conditions

It is recommended to avoid the exposure of **HERMACOLOR GREEN GR6016** to sunlight and high temperatures for longer times as this may impair the quality of the

HERMACOLOR GREEN GR6016.

Contact :

Hermess Compounds_Rue De Nabeul ZI M'Ghira 3_Ben Arous Tunisie
E-mail : resp.laboratoire@gmail.com / Tél : +216 58 59 71 74